

Product data sheet

A5000--F *



Electric strike with integrated wireless module

AREAS OF APPLICATION

- Standard and smoke protection doors
- Installation possible on left and right hand doors as well as horizontal or vertical
- Connection to direct or alternating current

PRODUCT FEATURES

- Approval for smoke protection doors
- Twin coil technology enables a larger operating voltage range
- Integrated bipolar EMC protective diode which protects connected electronic components against reverse voltage
- Integrated wireless module enables wireless activation
- Compact dimensions

TECHNICAL DATA

Productname	A5000--F *
Dimensions	15.8 x 79.4 x 25.5 mm
DIN direction	left / right
Set position x grid dimension	4 x 0.75 mm
Latch engagement depth	6.5 mm
Installation position vertical / horizontal	Yes
Fail-safe	No
Fail-secure	Yes
Dummy strike	No
Continuous operation voltage	12 V DC +/- 15 %
Approval for smoke protection doors	Yes
Mechanical release	No
Bipolar EMC protection diode integrated	Yes
Twin coil technology	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Dimensions	DIN direction	Type of installation
A5000--F compact electric strike	Functional principle: fail-secure / with integrated receiving module / Continuous operating stability: 12 V DC / Current consumption 200 mA / Dimensions (W x H x D): 15.8 x 80 x 25.5mm	144980	15.8 x 79.4 x 25.5 mm	left / right	in the door frame

A5000--F *



* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.